

# CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

#### Product Description

CR304 Urethane Slab Repair is a specially formulated hybrid urethane that allows for repairs of cracked, honeycombed, and spalled concrete in minutes. Its very low viscosity and self leveling nature allow for deep penetration into concrete cracks for a full and complete repair. It sets very rapidly and cures in approximately 15 minutes. Repaired areas can generally be ready for regular traffic in less than one hour. Once cured, it has a tensile strength of over 4000 PSI and provides for a permanent solution with excellent strength and durability. Repaired areas will have high impact and chemical resistance. CR304 can be combined with Silica Sand for repairing larger cracks. CR304 can be used on both interior and exterior surfaces. This product is not UV stable and cures to a tan color. For exterior surfaces, it is recommended that any repaired area also be treated with our CR305 Polyurea Crack & Joint Filler as a final step to provide UV stability.

#### Recommended Uses

CR304 is ideal for repairing hairline cracks as well as larger cracks in both commercial and residential structures such as workshop floors, warehouse floors, automotive garage floors, basement floors, garage floors, driveways, sidewalks, walkways, porches steps, pool decking, patios, etc. It is not recommended for repairing or sealing expansion joints.

#### Surface Preparation & Application

Concrete must be a minimum of 28 days old and/ or fully cured prior to use. The surface must be clean and dry prior to application. Refer to the Product Specifications Sheet for instructions prior to use.

BATCH # 123456

## URETHANE SLAB REPAIR

### Hybrid Urethane for Repairing Cracks in Concrete Slabs and Floors

- Professional Grade
- Two Component System
- Interior or Exterior

#### SHAKE WELL BEFORE USE

- ▶ Ultra Low Viscosity
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Deep Penetration
- ▶ Durable & Strong
- ▶ Fast Back in Service

#### CAUTION

Consult Material Safety Data Sheet prior to use. Wear glasses and gloves. Avoid contact with skin and eyes. Harmful if inhaled. May cause allergic skin and respiratory reaction. Vapor or mist may cause respiratory tract irritation.

#### ATTENTION

Avoid heat, open flame and sparks.

#### USE ONLY AS DIRECTED

#### FIRST AID

**EYES:** Flush with large amounts of water, minimum of 15 minutes. **SKIN:** Wash thoroughly with soap and water. Remove contaminated clothing. **INHALATION:** Leave area for fresh air. If not breathing, give artificial respiration and call physician. **INGESTION:** Do not induce vomiting. Seek medical care immediately.

**LIMITED WARRANTY** – The Manufacturer warrants products to be free from defects in material or manufacturing. Products are further warranted for adequacy of design when used in accordance with design limits, and properly specified and installed. This warrant does not apply to uses not in compliance with specific applications and installation procedures. All warranty obligations of the manufacturer shall be limited, at the discretion of the manufacturer, to repair or replacement of the defective product. These remedies shall constitute the manufacturer's sole obligation and sole remedy of purchaser under this warranty. In no event will the manufacturer be responsible for incidental, consequential, or specific loss or damage however caused.

#### Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300

info@concrete sealers usa.com | www.concrete sealers usa.com

# CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

#### Product Description

CR304 Urethane Slab Repair is a specially formulated hybrid urethane that allows for repairs of cracked, honeycombed, and spalled concrete in minutes. Its very low viscosity and self leveling nature allow for deep penetration into concrete cracks for a full and complete repair. It sets very rapidly and cures in approximately 15 minutes. Repaired areas can generally be ready for regular traffic in less than one hour. Once cured, it has a tensile strength of over 4000 PSI and provides for a permanent solution with excellent strength and durability. Repaired areas will have high impact and chemical resistance. CR304 can be combined with Silica Sand for repairing larger cracks. CR304 can be used on both interior and exterior surfaces. This product is not UV stable and cures to a tan color. For exterior surfaces, it is recommended that any repaired area also be treated with our CR305 Polyurea Crack & Joint Filler as a final step to provide UV stability.

#### Recommended Uses

CR304 is ideal for repairing hairline cracks as well as larger cracks in both commercial and residential structures such as workshop floors, warehouse floors, automotive garage floors, basement floors, garage floors, driveways, sidewalks, walkways, porches steps, pool decking, patios, etc. It is not recommended for repairing or sealing expansion joints.

#### Surface Preparation & Application

Concrete must be a minimum of 28 days old and/ or fully cured prior to use. The surface must be clean and dry prior to application. Refer to the Product Specifications Sheet for instructions prior to use.

BATCH # 123456

## URETHANE SLAB REPAIR

### Hybrid Urethane for Repairing Cracks in Concrete Slabs and Floors

- Professional Grade
- Two Component System
- Interior or Exterior

#### SHAKE WELL BEFORE USE

- ▶ Ultra Low Viscosity
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Deep Penetration
- ▶ Durable & Strong
- ▶ Fast Back in Service

#### CAUTION

Consult Material Safety Data Sheet prior to use. Wear glasses and gloves. Avoid contact with skin and eyes. Harmful if inhaled. May cause allergic skin and respiratory reaction. Vapor or mist may cause respiratory tract irritation.

#### ATTENTION

Avoid heat, open flame and sparks.

#### USE ONLY AS DIRECTED

#### FIRST AID

**EYES:** Flush with large amounts of water, minimum of 15 minutes. **SKIN:** Wash thoroughly with soap and water. Remove contaminated clothing. **INHALATION:** Leave area for fresh air. If not breathing, give artificial respiration and call physician. **INGESTION:** Do not induce vomiting. Seek medical care immediately.

**LIMITED WARRANTY** – The Manufacturer warrants products to be free from defects in material or manufacturing. Products are further warranted for adequacy of design when used in accordance with design limits, and properly specified and installed. This warrant does not apply to uses not in compliance with specific applications and installation procedures. All warranty obligations of the manufacturer shall be limited, at the discretion of the manufacturer, to repair or replacement of the defective product. These remedies shall constitute the manufacturer's sole obligation and sole remedy of purchaser under this warranty. In no event will the manufacturer be responsible for incidental, consequential, or specific loss or damage however caused.

#### Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300

info@concrete sealers usa.com | www.concrete sealers usa.com