

CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

URETHANE SLAB REPAIR

SHAKE WELL BEFORE USE

- ▶ Ultra Low Viscosity
- ▶ Deep Penetration
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Durable & Strong
- ▶ Fast Back in Service

**Hybrid Urethane for
Repairing Cracks in
Concrete Slabs and Floors**

CAUTION

Consult Material Safety Data sheet prior to use. Wear safety glasses and gloves. Avoid contact with skin and eyes. Avoid breathing vapors. Do not swallow

FIRST AID

EYES: Flush with large amounts of water, minimum of 15 minutes.

SKIN: Wash thoroughly with soap and water. Remove contaminated clothing.

INHALATION: Leave area for fresh air.

INGESTION: Do not induce vomiting. Seek medical help immediately.

USE ONLY AS DIRECTED

Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300
info@concretesealersusa.com | www.concretesealersusa.com

CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

URETHANE SLAB REPAIR

SHAKE WELL BEFORE USE

- ▶ Ultra Low Viscosity
- ▶ Deep Penetration
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Durable & Strong
- ▶ Fast Back in Service

**Hybrid Urethane for
Repairing Cracks in
Concrete Slabs and Floors**

CAUTION

Consult Material Safety Data sheet prior to use. Wear safety glasses and gloves. Avoid contact with skin and eyes. Avoid breathing vapors. Do not swallow

FIRST AID

EYES: Flush with large amounts of water, minimum of 15 minutes.

SKIN: Wash thoroughly with soap and water. Remove contaminated clothing.

INHALATION: Leave area for fresh air.

INGESTION: Do not induce vomiting. Seek medical help immediately.

USE ONLY AS DIRECTED

Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300
info@concretesealersusa.com | www.concretesealersusa.com

CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

URETHANE SLAB REPAIR

SHAKE WELL BEFORE USE

- ▶ Ultra Low Viscosity
- ▶ Deep Penetration
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Durable & Strong
- ▶ Fast Back in Service

**Hybrid Urethane for
Repairing Cracks in
Concrete Slabs and Floors**

CAUTION

Consult Material Safety Data sheet prior to use. Wear safety glasses and gloves. Avoid contact with skin and eyes. Avoid breathing vapors. Do not swallow

FIRST AID

EYES: Flush with large amounts of water, minimum of 15 minutes.

SKIN: Wash thoroughly with soap and water. Remove contaminated clothing.

INHALATION: Leave area for fresh air.

INGESTION: Do not induce vomiting. Seek medical help immediately.

USE ONLY AS DIRECTED

Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300
info@concretesealersusa.com | www.concretesealersusa.com