

CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

POLYUREA CRACK & JOINT FILLER

SHAKE WELL BEFORE USE

- ▶ UV Resistant
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Hard & Rubbery Texture
- ▶ Durable & Strong
- ▶ Fast Back in Service

UV Resistant Polyurea for Filling Cracks & Joints in Concrete Slabs and Floors

CAUTION

Consult Material Safety Data sheet prior to use. Wear safety glasses and gloves. Avoid contact with skin and eyes. Avoid breathing vapors. Do not swallow.

FIRST AID

EYES: Flush with large amounts of water, minimum of 15 minutes.

SKIN: Wash thoroughly with soap and water. Remove contaminated clothing.

INHALATION: Leave area for fresh air.

INGESTION: Do not induce vomiting. Seek medical help immediately.

USE ONLY AS DIRECTED

Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300
info@concretesealersusa.com | www.concretesealersusa.com

CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

POLYUREA CRACK & JOINT FILLER

SHAKE WELL BEFORE USE

- ▶ UV Resistant
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Hard & Rubbery Texture
- ▶ Durable & Strong
- ▶ Fast Back in Service

UV Resistant Polyurea for Filling Cracks & Joints in Concrete Slabs and Floors

CAUTION

Consult Material Safety Data sheet prior to use. Wear safety glasses and gloves. Avoid contact with skin and eyes. Avoid breathing vapors. Do not swallow.

FIRST AID

EYES: Flush with large amounts of water, minimum of 15 minutes.

SKIN: Wash thoroughly with soap and water. Remove contaminated clothing.

INHALATION: Leave area for fresh air.

INGESTION: Do not induce vomiting. Seek medical help immediately.

USE ONLY AS DIRECTED

Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300
info@concretesealersusa.com | www.concretesealersusa.com

CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

POLYUREA CRACK & JOINT FILLER

SHAKE WELL BEFORE USE

- ▶ UV Resistant
- ▶ Self Leveling
- ▶ Rapid Setting
- ▶ Hard & Rubbery Texture
- ▶ Durable & Strong
- ▶ Fast Back in Service

UV Resistant Polyurea for Filling Cracks & Joints in Concrete Slabs and Floors

CAUTION

Consult Material Safety Data sheet prior to use. Wear safety glasses and gloves. Avoid contact with skin and eyes. Avoid breathing vapors. Do not swallow.

FIRST AID

EYES: Flush with large amounts of water, minimum of 15 minutes.

SKIN: Wash thoroughly with soap and water. Remove contaminated clothing.

INHALATION: Leave area for fresh air.

INGESTION: Do not induce vomiting. Seek medical help immediately.

USE ONLY AS DIRECTED

Concrete Sealers USA

P.O. Box 5464 | De Pere, WI 54115

Toll-Free: 888.583.2991 | Fax: 920.759.5100 | Emergency: 800.424.9300
info@concretesealersusa.com | www.concretesealersusa.com